

Anti-Vandalism Tape

PVC

Overview


This anti-vandalism tape is fused to the interior of a trailer tarpaulin using hot air. Because this tape has a steel core, which is fused with the sail, it is virtually impossible to cut the exterior side of the semi-trailer sail open. Which means the theft of valuable cargo can be prevented.

DESIGN	 AV
MATERIAL	PVC Density IEC 60811-606 Tensile Strength ISO R 527 Elongation IEC 60811-501
INLAY	1.5 mm galvanised steel core 6x7
COLOR	Transparent, alu look
HARDNESS	77 (±3) (measured as Shore-A, at room temperature)
PACKAGING	 150 meter on cardboard reels suitable for Leister T1 welding equipment
DIMENSIONS	25x2,7 mm
HANDLING & STORAGE	Store away from direct sun light, heat or moisture sources. Temperature of handling the material is at room temperature [20°C 68°F]. To maintain the technical properties of the material unaltered it is recommended to keep the product in dry and ventilated storerooms.
DISCLAIMER	This information sheet has been created with the utmost care. Unless indicated otherwise, this sheet is solely intended to provide general information. It should not be relied on for any specific purpose and no representation or warranty is given as regards its accuracy or completeness.
PRODUCTION SALES CONDITIONS	Articles are produced in EEC. Conditions are deposited with KvK Eindhoven; 17060724.



Anti-Vandalism Tape

PVC

	Description	Dimension	Color*	Shape	Shore*	Packaging
ARTICLE CODE						
612.115.251	ANTI-VANDALISM TAPE Transparent Standard plus	25x2,7 mm	Transparent	AV 	Shore 77	150m on card-board reels, 36 reels in carton box
612.145.251	ANTI-VANDALISM TAPE Alu look Standard plus	25x2,7 mm	Alu look	AV 	Shore 77	150m on card-board reels, 36 reels in carton box

(* tolerance ± is applicable)

Other variations might be available upon request

